

GALAXY

HULK L-4

The Hulk has a unique tread pattern that allows it to operate in severe applications while providing superior self-cleaning characteristics. The Hulk has a minimum tread depth of 44/32nds and a lug-to-void ratio of 68% solid to 32% void. Because of the deep tread depth and solid-to-void ratio, the Hulk will provide extraordinary hours of service and reduces downtime due to cuts and punctures.

Le Hulk est doté d'un motif de semelle distinct qui lui permet de fonctionner dans des situations rigoureuses tout en fournissant des caractéristiques autonettoyantes supérieures. La profondeur des sculptures du Hulk est d'au moins 44/32e de pouce et un rapport vide-solide de 68 %- 32 %. En raison de la profondeur des sculptures et du rapport vide-solide, le Hulk fournira des heures de service innombrables et réduira les temps morts provoqués par les perforations et les coupures.

APPLICATIONS

- Skid Steer
- Mining
- Front Backhoe
- Rear Backhoe

UTILISATIONS

- Chargeurs compacts
- Exploitation minière
- Pelleteuse avant
- Pelleteuse arrière



CODE	SIZE	TYPE	PR	RIM	WT	NS	OD	SW	SLR	L.C.C.@AP	SP
										lbs@psi	
133260	10-16.5	TL	10	8.25	77	44	31.7	10.2	14.4	3,500@40	5
133266	12-16.5	TL	12	9.75	98	44	32.9	12.0	15.1	4,210@40	5
133273	33X1550-16.5	TL	14	12.00	117	44	33.1	15.1	15.1	4,830@35	5
133278	14-17.5	TL	14	10.50	130	46	36.0	13.8	16.5	5,260@35	5
202440-72	19.5L-24	TL	14	W16L	310	48	51.1	19.3	23.2	8,250@38	25

